PDS-GS0802T-ZC

8" industrial display



Features:

8“ industrial LCD

resolution 1024*768

multi-touch capacitive touchscreen

■ VGA/DVI/USB2.0

Specifications:

Display			
LCD panel	8″ LCD	Contrast ratio	1800：1
resolution	1024*768	Aspect ratio	4：3
brightness	400cd/m²		
touchscreen			
touchscreen type	capacitive touchscreen	Hardness	⩾6H
Light transmission	⩾85%		
Interface			
VGA	1*VGA	Audio	Line in
DVI	1*DVI	USB	1*USB 2.0(touchscreen)
OSD languages			
Menu languages	Chinese		
Power			
power input	DC5.5*2.5mm Power connector (standard 12/3A power adapter)		

Environment			
Vibration	5-19Hz/1.0mm amplitude; 19-200Hz/1.0g acceleration	Operating temp.	-10°C~60°C airflow over surface
Shock	10g acceleration, 11ms duration	Storage temp.	-20°C~70°C
Reliability	MTBF≥30000h; MTTR≤0.5h	Operating humidity	95%@40°C, non-condensing
IP rating	Front panel IP65		
Physical			
Dimensions (L x W x H)	227*173.6*40.7mm	Material	Aluminum alloy panel; all-metal design
Weight	1.45kg/2.1kg(net/gross)	Mounting	VESA mounting:75mm*75mm Panel cutout:202*161mm
Color	Black		

Dimensions:

