PDS-GS1001C-DE

10.1-inch industrial display



Features:

10.1-inch industrial LCD

Display resolution: 1280*800

10-point capacitive touchscreen

■ 1*VGA/1*HDMI/1*DVI/1*USB2.0

9~36V wide-voltage input

Specifications:

Display			
LCD panel	10.1” IPS LCD	Contrast ratio	800:1
resolution	1280*800	Aspect ratio	16:10
brightness	350cd/m²		
touchscreen			
touchscreen type	capacitive touchscreen	Hardness	⩾6H
Light transmission	⩾85%		
Interface			
VGA	1*VGA	Power connector	2-pin Phoenix terminal
HDMI	1*HDMI	Audio	1*Line out + 1*Audio in
DVI	1*DVI	USB	1*USB 2.0(touchscreen)
OSD languages			
Menu languages	English		
Power			
power input	9~36V input, Phoenix terminal (12V/5A adapter standard)		

Environment			
Vibration	5-19Hz/1.0mm amplitude; 19-200Hz/1.0g acceleration	Operating temp.	-10°C~60°C airflow over surface
Shock	10g acceleration, 11ms duration	Storage temp.	-20°C~70°C
Reliability	MTBF≥30000h; MTTR≤0.5h	Operating humidity	95%@40°C, non-condensing
IP rating	Front panel IP65		
Physical			
Dimensions (L x W x H)	290*210*36.2mm	Material	Aluminum alloy panel; all-metal design
Weight	1.65kg/2.05kg	Mounting	VESA mounting:100*100mm, 75*75mm
Color	Black		Panel cutout: 273*194mm

Dimensions:

