PDS-GS1201C-DE

12.1-inch industrial display



Features:

12.1-inch industrial LCD

Resolution: 1280*800

10-point capacitive touchscreen

■ 1*VGA/1*HD/1*DVI/1*USB2.0

9~36V wide-voltage input

Specifications:

Display			
LCD panel	12.1" LCD	Contrast ratio	1200：1
resolution	1280*800	Aspect ratio	16：10
brightness	500 cd/m²		
touchscreen			
touchscreen type	capacitive touchscreen	Hardness	⩾6H
Light transmission	⩾85%		
Interface			
VGA	1*VGA	Power connector	DC power jack or 2-pin Phoenix terminal
HD	1*HD	headphone jack	Line out + Mic in
DVI	1*DVI	Touch Interface	1*USB 2.0(touchscreen)
OSD languages			
Menu languages	English (other languages optional)		
Power			
power input	9~36V input, DC jack + 2-pin Phoenix terminal (12V/5A adapter standard)		

Environment			
Vibration	5-19Hz/1.0mm amplitude; 19-200Hz/1.0g acceleration	Operating temp.	-10°C~60°C airflow over surface
Shock	10g acceleration, 11ms duration	Storage temp.	-20°C~70°C
Reliability	MTBF≥30000h; MTTR≤0.5h	Operating humidity	95%@40°C, non-condensing
IP rating	Front panel IP65		
Physical			
Dimensions (L x W x H)	315.8*218*40.5mm	Material	Aluminum alloy panel; all-metal design
Weight	2.81kg/3.31kg (net/gross)	Mounting	VESA mounting:100*100mm, 75*75mm
Color	Black		Panel cutout: 205*303mm

Dimensions:

