PDS-GS1503T-BJ

15" industrial display





Features:

15" five-wire resistive touchscreen / industrial display

resolution 1024*768

■ 1*VGA/1*HDMI/1*DVI

1* front USB/1*USB(touchscreen)

1* front Switch

Specifications:

Display			
LCD panel	15" LCD	Contrast ratio	1000：1
resolution	1024*768	Aspect ratio	4：3
brightness	300 cd/m²		
touchscreen			
touchscreen type	resistive touchscreen	Hardness	⩾6H
Light transmission	⩾85%		
Interface			
VGA	1*VGA	Power connector	DC power input (optional Circular connector)
HD	1*HDMI	headphone jack	1*Line-out,1 Line-in
DVI	1*DVI	USB	2*USB(touchscreen / front USB)
OSD languages			
Menu languages	Chinese, English, German, French, Italian, Korean, Portuguese		
Power			
power input	12V DC input (9~36V wide-voltage module optional, standard 12/5A power adapter)		

Environment			
Vibration	5-19Hz/1.0mm amplitude; 19-200Hz/1.0g acceleration	Operating temp.	-10°C~60°C airflow over surface
Shock	10g acceleration, 11ms duration	Storage temp.	-20°C~70°C
Reliability	MTBF≥30000h; MTTR≤0.5h	Operating humidity	95%@40°C, non-condensing
IP rating	Front panel IP65		
Physical			
Dimensions (L x W x H)	400*290*46mm	Material	Aluminum alloy panel; all-metal design
Weight	5.6kg/6.8kg(net/gross)	Mounting	VESA mounting:100*100mm, 75*75mm
Color	Black		Panel cutout:377*267mm

Dimensions:

